

### Plant Protection Division Weights and Measures Program Metrology Laboratory

2747 29th Ave. SW ♦ Tumwater ♦ Washington 98512 Ph (360) 753-5042 + Fax (360) 586-4728 e-mail: dwright@agr.wa.gov



Under NVLAP Lab Code 200446-0

Report of Calibration # L2669-1

ile saltomber and Serial Number ....

Specification....: NIST HB 105-8

Date Received...: November 13, 2007

Work Order #...: L2669-1-

Manufacture ....: Weight Cart, Inc.

Material..... Cast Iron Seal Number ....: 0264701

Submitted By

Washington State Patrol 8623 Armstrong Road SW

Olympia, WA 98504

Purchase Order # : N/A

Point of Contact ...: Dave Cromer Phone #..... (360) 596-6000

**Artifact Calibration Results** 

Weight Description	CM Correction As Found (lb)	CM Correction As Left (lb)	Class Weight Cart Tolerance ± (lb)	Uncertainty k=2 (lb)	
4000 lb	-15.85	-0.33	1.25	0.42	

#### **Calibration Notes**

- The artifact(s) listed above have been found and/or left within the stated tolerances for the classification(s) stated above, except as noted. An artifact is considered in-tolerance when the correction plus the measurement uncertainty is equal to or less than the specified tolerance. Bold print indicates an out-of-tolerance reading.
- All corrections stated in this report correlate to a "Conventional Mass" (CM), also known as 'apparent mass", scale verses 8.0 g/cm³ reference mass density and an air density of 1.2 mg/cm3 at 20 °C.

#### **Calibration Conditions**

Technician............ Dan Wright

Condition of Artifact: Good

Temperature...... 19.9 °C

Procedure: NIST HB 145, SOP 4

Humidity: 38.7 % RH Pressure: 760.2 mm Hg

Laboratory Standard(s) Used

Description	Serial Number	Report Number	Date Calibrated	Date Calibration Due
2000 lb Mass Standards	SP2 & SP3	L2669-3	11/16/2007	11/16/2009
2000 lb Mass Standards	SP7 & SP11	L2669-3	11/16/2007	11/16/2009



# Plant Protogrammers Programmers Metrology Laboratory

2747 29th Ave. SW ♦ Tumwater ♦ Washington 98512 Ph (360) 753-5042 ♦ Fax (360) 586-4728 e-mail: dwright@agr.wa.gov

For Scope of Accreditates
Under
NVLAP Lab Code 200446-0

#### Report of Calibration # L2669-1

#### **Relevant Information**

- Liquid levels, as stated on the attached Weight Cart Inspection Checklist, must be maintained as close to reference levels as possible during use.
- The attached Weight Cart Inspection Checklist is an integral component of this Report of Calibration and a copy must be maintained with the cart and reviewed prior to use.
- Any maintenance, repairs, replacement of parts, or damage to the weight cart or its components will likely result in an
  out-of-tolerance condition. Maintenance or replacement of components such as batteries, tires, filters, or other items
  listed on the attached Weight Cart Inspection Checklist will require calibration of the weight cart prior to subsequent
  use.
- The results listed in this report relate only to the artifacts described and extent of calibrations performed.

#### **Traceability Statement**

The item(s) listed above have been compared to the Standards of the State of Washington. The Standards of the State of Washington are traceable to the National Institute of Standards and Technology (NIST) and are part of a comprehensive measurement assurance program for ensuring continued accuracy and measurement traceability within the level of uncertainty reported by this laboratory. The report of calibration number identified in the title of this report is the unique report number to be used in referencing measurement traceability for the artifact(s) identified in this report only.

#### **Uncertainty Statement**

The combined standard uncertainty includes uncertainties reported for the standard, uncertainties associated with the measurement process, uncertainties for any observed deviations from reference values which are less than surveillance limits, and other uncertainties associated with the particular artifact (i.e., reading meniscus, air buoyancy corrections, etc.). The combined standard uncertainty is multiplied by k, a coverage factor of 2, to give the expanded uncertainty (which defines an interval with an approximate 95 percent level of confidence). The expanded uncertainty presented in this report is consistent with NIST Technical Note 1297. Stated uncertainties are less than 1/3 of the applicable tolerances. Magnetic testing has not been performed and there are no components for the effects of magnetism in the uncertainty budget.

#### **Certification Statement**

Accredited by the National Institute of Standards and Technology (NIST) through the National Voluntary Laboratory Accreditation Program (NVLAP) for the specified scope of accreditation under lab code 200446-0. This laboratory meets the requirements of ISO/IEC 17025 and ANSI/NCSL Z540-1. This report may not be used to claim product endorsement by NVLAP or any other government agency, and may not be reproduced, except in full, without written approval from the laboratory.

I certify (or decla	are) under penalty of pe	erjury under t	the laws of the State	of Washington	that the foregoing	is true and correc
Executed this	19-6	day of	November	at Tumwater,	Thurston County,	Washington

Dan Wright, State Metrologist



## Weight Cart Inspection Checklist

AGRICULTURE	WANIKF-UII	4/5/03				
COMPANY Washington State Patr	ol		ION DATE 1ber 19, 2007	STATE TEST NO. L2669-1		
ADDRESS 8623 Armstrong Road	sw	<u>Nomina</u> 4000 II	L VALUE b	MODEL NUMBER WC-20k		
Olympia, WA 98504		CTURER t Carts, Inc.	SERIAL NUMBER 103-2-90			
POINT OF CONTACT Dave Cromer			PHONE NUMBER 360-596-6000			
Power:	Electric Battery	√ 🔀 💠 Elec	tric Generator 🗌 💠 (	Gasoline 🗌 💠 Diesel 🗌		
Fluids: 🔲 En	Fluids: Engine Oil			Reference Level:		
□ну	draulic Oil	Sealed? Yes	□ No □	Reference Level:		
⊠ Ba	ttery	Sealed? Yes	□ No ⊠	Reference Level: @ lip		
☐ Fu	☐ Fuel Sig		Gauge? Yes No Reference Level:			
Number of axles	: 2					
Number / Size of	f Tires: 2 @ 15 X	X 6 X 11 1/4 a	and 2 @ 21 X 7 X 15			
Nominal mass of	f weight cart is s	uitably marke	d. Yes 🛛 No 🗌			
Do fluid drain tubes extend beyond the body of the cart? Yes  No NA						
	Sealed wheel bearings. Yes 🛛 No 🗌					
		· · · · · · · · · · · · · · · · · · ·	ay accumulate. Yes 🗵	No []		
	Weight restraint railing permanently fixed and solid. Yes 🔀 No 🗌					
			Approximate capacity:	20 lb		
Adjusting cavity						
Service brakes a		<del></del>				
Parking brakes a		<u> </u>		<u> </u>		
Remote control i						
General condition at time of calibration (i.e., any accumulated dirt/debris, damage, loose parts, or evidence of tampering or unauthorized entry of seals): Good						
List and report any repair and/or maintenance performed (i.e., leaks repaired, parts replaced, wheels changed, welding performed, etc.) since the last calibration: Batteries Replaced						
\						
Authorized Signature: Way Way W						